




FÖRDERANLAGEN - BELT CONVEYORS GTK PÁSOVÉ DOPRAVNÍKY

GTK, spol s r.o., CZ-687 07 TUPESY 116, okres Uherské Hradiště, Česká republika

Tel.: +420 572 520 880-9, Fax: +420 572 520 899

Idler frames

Version:



BB(mm)	Inclination°	D(mm)	RL(mm)	h(mm)	A(mm)	E(mm)	a(mm)	b(mm)	m(kg)	Artikl
1200	15	108,133,159	465	165	1530	1590	30	65	36.50	U1612015165
1200	20	108,133,159	465	165	1530	1590	30	65	37.10	U1612020166
1200	25	108,133,159	465	165	1530	1590	30	65	37.90	U1612025165
1200	30	108,133,159	465	165	1530	1590	30	65	38.50	U1612030165
1200	35	108,133,159	465	165	1530	1590	30	65	39.60	U1612035165
1200	40	108,133,159	465	165	1530	1590	30	65	40.40	U1612040165
1200	45	108,133,159	465	165	1530	1590	30	65	41.00	U1612045165
1400	15	108,133,159	530	165	1730	1790	30	65	40.50	U1614015165
1400	20	108,133,159	530	165	1730	1790	30	65	41.20	U1614020166
1400	25	108,133,159	530	165	1730	1790	30	65	42.10	U1614025165
1400	30	108,133,159	530	165	1730	1790	30	65	43.00	U1614030165
1400	35	108,133,159	530	165	1730	1790	30	65	43.80	U1614035165
1400	40	108,133,159	530	165	1730	1790	30	65	44.90	U1614040165
1400	45	108,133,159	530	165	1730	1790	30	65	45.70	U1614045165
1600	15	108,133,159	600	165	1980	2040	30	65	45.50	U1616015165
1600	20	108,133,159	600	165	1980	2040	30	65	46.20	U1616020165
1600	25	108,133,159	600	165	1980	2040	30	65	47.20	U1616025165



GTK spol. s r.o., CZ-68707 Tupesy 116, Czech Republik, Tel.: +420 572 520 880-9, Fax: +420 520 899
e-mail: gtk@gktupesy.cz, www.gktupesy.cz





FÖRDERANLAGEN - BELT CONVEYORS GTK PÁSOVÉ DOPRAVNÍKY

GTK, spol s r.o., CZ-687 07 TUPESY 116, okres Uherské Hradiště, Česká republika

Tel.: +420 572 520 880-9, Fax: +420 572 520 899

1600	30	108,133,159	600	165	1980	2040	30	65	48.20	U1616030165
1600	35	108,133,159	600	165	1980	2040	30	65	49.10	U1616035165
1600	40	108,133,159	600	165	1980	2040	30	65	50.30	U1616040165
1600	45	108,133,159	600	165	1980	2040	30	65	51.20	U1616045165
1800	15	108,133,159	670	165	2180	2240	30	65	49.70	U1618015165
1800	20	108,133,159	670	165	2180	2240	30	65	50.40	U1618020165
1800	25	108,133,159	670	165	2180	2240	30	65	51.60	U1618025165
1800	30	108,133,159	670	165	2180	2240	30	65	52.60	U1618030165
1800	35	108,133,159	670	165	2180	2240	30	65	53.70	U1618035165
1800	40	108,133,159	670	165	2180	2240	30	65	54.90	U1618040165
1800	45	108,133,159	670	165	2180	2240	30	65	55.90	U1618045165
2000	15	108,133,159	750	165	2420	2490	35	75	54.70	U1620015165
2000	20	108,133,159	750	165	2420	2490	35	75	55.70	U1620020165
2000	25	108,133,159	750	165	2420	2490	35	75	57.00	U1620025165
2000	30	108,133,159	750	165	2420	2490	35	75	58.00	U1620030165
2000	35	108,133,159	750	165	2420	2490	35	75	59.30	U1620035165
2000	40	108,133,159	750	165	2420	2490	35	75	60.60	U1620040165
2000	45	108,133,159	750	165	2420	2490	35	75	61.60	U1620045165



GTK spol. s r.o., CZ-68707 Tupesy 116, Czech Republik, Tel.: +420 572 520 880-9, Fax: +420 520 899
e-mail: gtk@gktupesy.cz, www.gktupesy.cz

